

⑩



Europäisches Patentamt
European Patent Office
Office européen des brevets

⑪ Publication number:

**0 024 148
B1**

⑫

EUROPEAN PATENT SPECIFICATION

⑬ Date of publication of patent specification: 13.02.85

⑭ Int. Cl.⁴: **B 01 D 19/00, E 21 B 43/34,
C 10 G 33/06**

⑮ Application number: 80302632.7

⑯ Date of filing: 01.08.80

BEST AVAILABLE COPY

⑰ Separator for oil, gas and water.

⑱ Priority: 09.08.79 GB 7927806

⑲ Date of publication of application:
25.02.81 Bulletin 81/08

⑳ Publication of the grant of the patent:
13.02.85 Bulletin 85/07

㉑ Designated Contracting States:
DE FR GB IT NL

㉒ References cited:
FR-A-1 565 069
GB-A-2 000 054
US-A-2 767 802
US-A-3 045 750
US-A-4 072 481

㉓ Proprietor: The British Petroleum Company
p.l.c.
Britannic House Moor Lane
London EC2Y 9BU (GB)

㉔ Inventor: Davies, Evan E. The British Petroleum
Company Ltd.
Britannic House Moor Lane
London EC2Y 9BU (GB)
Inventor: Nebrensky, J.R. The British Petroleum
Company Ltd.
Britannic House Moor Lane
London EC2Y 9BU (GB)

㉕ Representative: Crack, Richard David et al
c/o The British Petroleum Company plc Patents
Division Chertsey Road
Sunbury-on-Thames Middlesex, TW16 7LN (GB)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European patent convention).

Courier Press, Leamington Spa, England.

EP 0 024 148 B1

Description

This invention relates to a separator suitable for separating oil containing gas and water into gas and two liquid streams one being an oil rich stream the other a water rich stream.

When oil is produced from a well, it is forced from the reservoir by natural pressure up the well to the surface. As the oil rises the pressure becomes less and gas associated with the oil is progressively released from solution.

After emerging from the well, it is necessary to treat the mixture of liquid oil and gas to remove the free gas and dissolved gas which is likely to come out of solution when the oil is maintained at about atmospheric pressure as, for example, during transport in a tanker.

Our UK Patent Application No. 2000054A describes a cyclone separator capable of separating such a mixture the cyclone having a cone located therein and our co-pending UK Patent Application No. 2035150A describes a cyclone separator which has been improved by the provision of baffles below the cone. Further, our co-pending European Patent Application No. 80301144.4 describes a cyclone separator which has been further improved by the cone being in the form of one of small apex angle or as a cylinder.

Water, the amount of which can vary greatly, is usually also produced with the oil and it is desirable to also remove the water since the latter is often saline and may well cause corrosion of steel production facilities. However, with the separators disclosed in the three above mentioned patents water, if present in the feed, is separated within the liquid oil.

French patent specification 1,565,069 discloses a liquid/gas cyclone separator in which a splash ring 40 is designed to alter the direction of flow of liquid. Vertical isolation plates 44 suspended from the ring provide a quiescent zone in which a normal gravity separation can take place.

According to the present invention, there is provided a cyclone separator for separating a crude oil stream containing gas, oil and water into separate streams of oil, water and gas comprising a vessel having an inlet disposed so that the feed introduced under a pressure gradient is caused to form a downwardly flowing vortex of liquid from which the gas separates, an upper outlet for the gas comprising a pipe extending downwardly into the vessel, a downwardly extending hollow small angle cone or cylinder located below the inlet and disposed so that its internal surface provides a surface for the downwardly flowing vortex of liquid, the walls of the vessel being spaced apart from the cone or cylinder to define therebetween a disengaging chamber, a baffle being located below the lower end of the cone or cylinder to arrest the vortex of gas, the vessel being sized so as to allow the downwardly flowing liquid to separate into an oil rich liquid layer and a water rich liquid layer,

a first lower outlet for the discharge of the oil rich liquid and a second lower outlet for the discharge of the water rich liquid spaced apart from and below the first lower outlet wherein there is located below the first lower outlet a conical deflector plate, having top and bottom outlets, to assist in keeping the oil and water layers separate and to deflect downwardly flowing water towards the walls of the vessel and to deflect upwardly flowing oil towards the first lower outlet.

The conical deflector plate does not interrupt nor change the direction of flow of the liquids.

Conveniently a level sensor is provided for sensing the oil level in the vessel and control means are provided for controlling the flow from the first lower outlet and/or second lower outlet in response to said oil level.

Conveniently a further level sensor is provided for sensing the water level and control means are provided for controlling the flow from the first lower outlet and/or second lower outlet in response to said water level.

The ratio of the diameter of the upper outlet pipe to that of the vessel in the region of the inlet can be from 0.40 to 0.80, conveniently from 0.55 to 0.75. The upper outlet pipe can extend into the vessel below the centre line of the inlet and can conveniently terminate at a level intermediate the centre line of the inlet and the upper end of the cone.

The upper outlet pipe can have in the region of the lower end thereof a flared portion herein referred to as a skirt, to reduce the amount of liquid entrained in the gas flowing upwardly in the vortex finder.

References in the present specification to lower, upper and vertical refer to the separator in its disposition for normal use.

Conveniently the first lower outlet for the oil rich liquid is in the form of a pipe extending into the vessel through the wall thereof to withdraw liquid from a region below the lower end of the cone and conveniently near the axis of the vessel.

The second lower outlet can also be in the form of a pipe extending through the wall of the vessel and can be disposed to withdraw liquid from a region near the base of the vessel. The outlet can be provided by an aperture in the region of the base of the vessel.

In operation the flow through the outlets is preferably controlled to maintain a steady oil level and a steady water level in the disengaging chamber.

The inlet to the vessel is preferably rectangular in cross-section to assist tangential entry.

Since the feedrate may vary it is desirable to have means for controllably adjusting the size of the inlet comprising an adjustable shutter to restrict the inlet, for example, as described in our UK Patent Application No. 2000054A and our co-pending UK Patent Application No. 203150A.

If necessary provision may be made for injecting a demulsifier or defoaming agent, e.g. a silicone oil, at any convenient point.

The disengaging chamber may be provided by an enlarged lower portion of the vessel.

In the case of a vessel whose horizontal section is circular the diameter of the enlarged portion may be conveniently 1.2 to 2.0 that of the upper portion.

In the present specification the volume within the vessel below where conical surface terminates is considered to be part of the disengaging chamber.

The feed may also contain solids which are normally present in crude oil in the amounts in which they are normally present. Such solids are separated with the water rich liquid stream.

The feed may have a gas:liquid ratio of from 1.5:1 to 15:1 and may optionally contain water in amount up to 50% or more (both amounts being by volume referred to the feed at separation conditions) and the pressure inside the vessel can be from 1 to 120 bar absolute and inlet velocities to the vessel can be from 5 to 250 m/sec and the process can involve controlling the operating conditions within the ranges specified to obtain a separated gas not more than 10 ppm vol of liquid and a separated oil rich liquid containing more than 2% water and a water rich liquid containing not more than 5% oil (both % being by vol).

In many cases it is preferred to control the inlet velocity to the vessel in the range 8 to 70 m/sec to improve vortex formation.

Desirably the oil level in the vessel is controlled to be as high as possible consistent with there being no measurable carry over of oil in the gas. When there is oil carry over, the oil content of the gas which is normally below 1 ppm (part per million) rises rapidly. Similarly, if the oil level is too low then there may be gas in the liquid oil and the gas content of the oil, normally below 15% by volume, will rise.

Preferably the separator vessel includes means for controlling the oil level within the above mentioned limits.

Preferably the separator vessel also includes means for controlling the water level so that the water content of the oil does not exceed 2% vol and the oil content of the water does not exceed 5% vol.

The invention is illustrated by reference to the accompanying drawings in which Figure 1 is a vertical section of one embodiment of cyclone separator and Figure 2 is an elevation partly cut away of an alternative embodiment of cyclone separator. Figure 3 is a vertical section of an alternative embodiment of cyclone separator (in which the water outlet is in a different position) and also showing schematically the oil and water level controls. Although not shown in the drawings the embodiments include the adjustable shutter to restrict the inlet as described in our UK Patent Application Nos. 2000054A and 2035150A.

Referring to Figure 1 the separator indicated generally by reference numeral 2 comprises a vessel 4 having an inlet 6 of rectangular cross-section disposed tangentially with respect to the vessel 4 to cause incoming feed to form a downwardly spinning vortex of enhanced liquid from which an upwardly spinning vortex of enhanced gas separates. The inlet is controllably variable as described in our co-pending UK Patent Applications Nos. 2000054A and 2035150A to provide a turndown capacity and to accommodate changes in feed composition. The separator has an outlet for gas herein referred to as a vortex finder 8 leading to an outlet pipe 10, and a hollow truncated cone 12 of small angle (the angle at the apex of the cone is 3°) to provide a surface for the downwardly spinning vortex. The ratio of the diameter of the cone at its lower end to that at its upper end is 0.88. A disengaging chamber 15 is provided by the space between cone 12 and the walls 7 of the lower part of the vessel and an outlet 20 for withdrawing gas from the disengaging chamber 15 is provided so that gas not separated from the liquid in the centrifugal action in the cone does not interfere with the liquid level control.

The disengaging chamber 15 is also provided with a pressure relief valve 26.

Located transversely with respect to the axis of the cone 12 and a small distance below the lower end thereof is a baffle in the form of a circular plate 14, the purpose of which is to arrest the vortex of gas. Means are provided, (not shown), for moving the plate up or down to adjust the size of the gap between the lower end of the cone and the plate to optimise the performance of the separator. Below the plate 14 is a first lower outlet 16 for the liquid oil, arranged so that liquid is withdrawn from below the axis of the outlet to reduce the risk of entrainment of gas in the oil during discharge. Below outlet 16 is a partition 22 in the form of a hollow truncated cone, the axis of the cone lying on the axis of the vessel. The cone is disposed so as to allow water to flow on its upper surface downwardly and outwardly towards the walls of the vessel and into the portion of the vessel below the partition. Below the partition 22 is a second lower outlet 18 for the water rich liquid stream disposed in a manner similar to outlet 16.

A set of straightening vanes, (not shown), are included in the outlet pipe 10 to eliminate any spinning of the gas.

The vortex finder 8 has a flared portion to provide a skirt 9 to reduce the tendency of droplets of liquid on the exterior to be entrained in the gas flowing upwardly into the vortex finder.

The vessel has two connections only one of which 28 is shown for an oil level controller, (not shown), and connections 30 and 31 for a water level controller, (also not shown). At the bottom of the vessel is a drain hole 24.

Referring to Figure 2 the separator indicated

generally by reference numeral 42 comprises a vessel 44 having an inlet 46 of rectangular cross-section disposed tangentially with respect to the vessel 44 to cause incoming feed to form a downwardly spinning vortex 41 from which gas separates. The inlet 46 is controllably variable as described in our co-pending UK Patent Applications Nos. 2000054A and 2035150A to provide a turndown capacity. The separator has a vortex finder 48 leading to an outlet pipe, (not shown), and a hollow inverted truncated cone of small angle 52 (the angle at the apex of the cone is 3°) to provide a surface and a downwardly spinning vortex 41. The ratio of the diameter of the cone 52 at its lower end to that at its upper end is 0.88.

A set of straightening vanes, (not shown), are included in the outlet pipe, (not shown), to eliminate any spinning of the gas.

A disengaging chamber 55 is provided by the space between cone 52 and the walls 47 of the lower part of the vessel and an outlet 60 for withdrawing gas from the disengaging chamber 55 is provided so that gas not separated from the liquid in the centrifugal action in the cone 52 does not interfere with the liquid level control.

The disengaging chamber 55 is also provided with a pressure relief valve, (not shown).

Located transversely with respect to the axis of the cone 52 and a small distance below the lower end thereof is a baffle 54 in the form of a circular plate 54, the purpose of which is to arrest the vortex 41. Means are provided, (not shown), for moving the plate 54 up or down to adjust the size of the gap between the lower end of the cone 52 and the plate 54 to optimise the performance of the separator. Below the plate 54 is a first lower outlet 56 for the liquid oil, arranged so that liquid is withdrawn from below the axis of the outlet to reduce the risk of

entrainment of gas in the oil during discharge. Below outlet 56 is a deflector 62 in the form of a hollow truncated cone, the cone being coaxial with the vessel 44. The cone 62 is disposed so as to allow water to flow on its upper surface downwardly and outwardly towards the walls 47 of the vessel and away from the oil outlet into the portion of the vessel below the deflector. Below the deflector 62 is a second lower outlet 68 for the water rich liquid stream. Droplets of oil can flow upwards within the deflector into the oil phase above interface 70 through the aperture at the top of the cone 62.

The vortex finder 48 has a flared portion (not shown) to provide a skirt to reduce the tendency of droplets of liquid on the exterior to be entrained in the gas flowing upwardly into the vortex finder 48. An oil/gas interface at 72 is normally maintained above the lower end of cone 52.

Referring to Figure 3 the separator indicated generally by numeral 82 comprises a vessel 84 of similar construction to that shown in Figure 1 except the outlet 88 for the water is located nearer the base of the vessel 84. The vessel 84 has an oil level sensor 90 and a water level sensor 91 and control means comprising valves 93 and 94 controlling the flow in lines 95 and 96, the valves 93 and 94 being operated in response to signals indicative of the oil and water levels.

Example 1

Use of a single cyclone

The cyclone separator was a single vessel as illustrated in Figure 1, and was operated with the oil/gas and oil/water interfaces as shown in Figure 2.

The operating conditions and performance data are summarised in the following table.

45

50

55

60

65

4

0024 148

Feed

Total rate*	m ³ /hr	650 (equivalent to 12,000 bbl/day of liquid+gas)
Oil flow	m ³ oil/hr (bbl/day)	66.2 10,000
Temperature	°C	40
Inlet pressure	bar abs	42.4
Equilibrium gas content	vol %	87.8
Gas/oil ratio*	vol/vol	7.2
Water content in the liquid	% by vol	16.6

*assumes equilibrium state

Products

Liquid from 1st lower outlet

Total rate	m ³ /hr	76.7
Water content	vol %	2.0
Oil content	vol %	84.0

The liquid contained 12.0% volume of gas.

Liquid from 2nd lower outlet

Total rate	m ³ /hr	12.5
Oil content	vol %	1.9
Water content	vol %	93.1

The liquid contained 5% volume of gas.

Gas from vortex finder

Total rate at outlet	m ³ /hr	595
Pressure	bar	40 bar absolute
Liquid (oil & water) content	ppm	1

This Example illustrates that a separator according to the invention can separate a mixture of liquid oil with 7.2 times its own volume of gas and 16.6% its own volume of

water into (i) a liquid oil containing 2% by volume of water and 12.0% by volume of gas, (ii) water containing 1.9% by volume of oil and (iii) gas containing less than 1 ppm of liquid.

55

60

65

5

Example 2

The cyclone was a single vessel as illustrated in Figure 1 but of smaller size than that employed in Example 1.

Feed-litres/hour

Gas	93.3	Temperature 21°C
Liquid oil	19.2	Inlet pressure 1.7 bar absolute
Water	4.2	
Total	116.7	
Vortex finder pressure	1.5 bar absolute	

Products-litres/hour

From 1st lower outlet

Oil	19.2 containing 21.2 litres/hr of gas 0.35 litres/hr of water
-----	--

From 2nd lower outlet

Water	3.83
Oil	71×10^{-6} (≈ 18 ppm of oil)
No gas	

From vortex finder

Gas	72.1 containing less than 1 ppm of liquid.
-----	---

The separator according to the present invention is particularly suitable for use as a well test separator where the mixture to be separated may be frequently contain water from drilling mud left in the well.

Unless the context clearly requires otherwise, references to volumes of gas and gas to liquid ratios are referred to standard conditions of temperature and pressure i.e. 14.7 psig (1013 bar absolute) and 60°F equivalent to 15.6°C.

Claims

1. A cyclone separator (2) for separating a crude oil stream containing gas, oil and water into separate streams of oil, water and gas comprising a vessel (7) having an inlet (6) disposed so that the feed introduced under a pressure gradient is caused to form a downwardly flowing vortex of liquid (41) from which the gas separates, an upper outlet for the gas comprising a pipe (8) extending downwardly into the vessel (7), a downwardly extending hollow small angle cone or cylinder (12) located below the inlet (6) and disposed so that its internal surface provides a surface for the downwardly flowing vortex of liquid (41), the walls of the vessel (7) being spaced apart from the cone or

cylinder (12) to define therebetween a disengaging chamber (15), a baffle (14) being located below the lower end of the cone or cylinder (12) to arrest the vortex of gas, the vessel being sized so as to allow the downwardly flowing liquid to separate into an oil rich liquid layer and a water rich liquid layer, a first lower outlet (16) for the discharge of the oil rich liquid and a second lower outlet (18) for the discharge of the water rich liquid spaced apart from and below the first lower outlet (16), characterised in that there is located below the first lower outlet (16) a conical deflector plate (22), having top and bottom outlets, so assist in keeping the oil and water layers separate and to deflect downwardly flowing water towards the walls of the vessel (7) and to deflect upwardly flowing oil towards the first lower outlet (16).

2. A cyclone separator according to claim 1, characterised in that a level sensor (90) is provided for sensing the oil level (72) and control means (93, 94) for controlling the flow from outlets (16) and/or (18) in response to the level.

3. A cyclone separator according to either of the preceding claims characterised in that a level sensor (91) is provided for sensing the water level (70) and control means (93, 94) for

controlling the flow from outlets (16) and/or (18) in response to the level.

Patentansprüche

1. Zyklon-Abscheider (2) zur Auftrennung eines Gas, Öl und Wasser enthaltenden Rohöl-Stroms in getrennte Öl-, Wasser- und Gas-Ströme mit einem Gefäß (7) mit einer derart angeordneten Einlaßöffnung (6), daß dem unter einem Druckgradienten eingeführten zufließenden Material die Bildung eines abwärts fließenden Flüssigkeitswirbels (41) aufgezwungen wird, aus dem sich das Gas abscheidet, einer oberen Auslaßöffnung für das Gas aus einem Rohr (8), das nach unten in das Gefäß (7) hinein reicht, einem sich nach unten erstreckenden kleinwinkligen Hohlkegel oder -zylinder (12), der unterhalb der Einlaßöffnung (6) liegt und so angeordnet ist, daß seine innere Oberfläche eine Fläche für den abwärts fließenden Flüssigkeitswirbel (41) bildet, wobei die Wandungen des Gefäßes (7) sich in einem gewissen Abstand von dem Kegel oder Zylinder (12) befinden, wodurch dazwischen eine Abtrennkammer (15) gebildet wird, einer Stauplatte (Baffle) (14), die unterhalb des unteren Endes des Kegels oder Zylinders (12) angeordnet ist, um den Gaswirbel zurückzuhalten, wobei die Größe des Gefäßes so bemessen ist, daß eine Trennung der abwärts fließenden Flüssigkeit in eine ölige Schicht und eine wasserreiche Schicht ermöglicht wird, einer ersten unteren Auslaßöffnung (16) für den Austrag der ölige Flüssigkeit und, in einem gewissen Abstand und unterhalb von dieser ersten unteren Auslaßöffnung (16), einer zweiten unteren Auslaßöffnung (18) für den Austrag der wasserreichen Flüssigkeit, dadurch gekennzeichnet, daß unterhalb der ersten unteren Auslaßöffnung (16) eine kegelförmige Umlenkplatte (22) mit Auslaßöffnungen auf der Ober- und Unterseite angebracht ist, um die Beibehaltung der Trennung zwischen ölschicht und Wasserschicht zu unterstützen und das abwärts fließende Wasser in Richtung auf die Wandungen des Gefäßes (7) umzulenken und das aufwärts fließende Öl in Richtung auf die erste untere Auslaßöffnung (16) umzulenken.

2. Zyklon-Abscheider nach Anspruch 1, dadurch gekennzeichnet, daß ein Standhöhen-Sensor (90) zum Fühlen der Öl-Standhöhe (72) und Steuerungsmittel (93; 94) für die Steuerung der Ströme aus den Auslaßöffnungen (16) und/oder (18) als Antwort auf den Wert der Standhöhe angebracht sind.

3. Zyklon-Abscheider nach einem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß ein Standhöhen-Sensor (91) zum Fühlen der Wasser-Standhöhe (70) und Steuerungs-

mittel (93; 94) für die Steuerung der Ströme aus den Auslaßöffnungen (16) und/oder (18) als Antwort auf den Wert der Standhöhe angebracht sind.


Revendications

1. Séparateur à cyclone (2) pour séparer un courant d'huile brut contenant du gaz, de l'huile et de l'eau en des courants séparés d'huile, de gaz et d'eau, comprenant un récipient (7) comportant une entrée (6) disposée de manière à ce que le produit amené introduit avec un gradient de pression soit amené à former un tourbillon de liquide (41) s'écoulant vers le bas, duquel le gaz se sépare, une sortie supérieure pour le gaz, comprenant un tuyau (8) s'étendant vers le bas dans le récipient (7), un cône de petit angle ou cylindre creux (12) s'étendant vers le bas, situé au dessous de l'entrée (6) et disposé de manière à ce que sa surface interne définisse une surface pour le tourbillon de liquide (41) s'écoulant vers le bas, les parois du récipient (7) étant espacées du cône ou cylindre (12) pour définir entre ceux-ci une chambre de dégagement (15), une chicane (14) étant située au dessous de l'extrémité inférieure du cône ou cylindre (12) pour arrêter le tourbillon de gaz, le récipient étant dimensionné de manière à permettre au liquide s'écoulant vers le bas de se séparer en une couche de liquide riche en huile et une couche de liquide riche en eau, une première sortie inférieure (16) pour l'évacuation du liquide riche en huile et une seconde sortie inférieure (18) pour l'évacuation du liquide riche en eau, espacée et située au dessous de la première sortie inférieure (16), caractérisé en ce qu'une plaque déflectrice conique 22 est située au dessous de la première sortie inférieure (16), plaque comportant des sorties supérieure et inférieure, destinée à aider à maintenir les couches d'huile et d'eau séparées et à dévier vers le bas l'eau s'écoulant vers les parois du récipient (7) et à dévier vers le haut l'huile s'écoulant vers la première sortie inférieure (16).

2. Séparateur à cyclone selon la revendication 1, caractérisé en ce qu'un détecteur de niveau (90) est prévu pour détecter le niveau d'huile (72), ainsi que des moyens de commande (93, 94) pour contrôler l'écoulement à partir des sorties (16) et/ou (18) en réponse au niveau.

3. Séparateur à cyclone selon l'une ou l'autre des revendications précédentes, caractérisé en ce qu'un détecteur de niveau (91) est prévu pour détecter le niveau d'eau (70), ainsi que des moyens de commande (93, 94) pour contrôler l'écoulement à partir des sorties (16) et/ou (18) en réponse au niveau.

FIG.1.







FIG.3



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.